Concours®14 ABS









P	N	V	V	F	R
•					-

4-stroke, 4-cylinder, DOHC, 4-valve, liquid-**Engine**

cooled

Displacement 1,352cc

Bore x Stroke 84.0 x 61.0mm

Compression

Ratio

10.7:1

Fuel System DFI® with 40mm throttle bodies (4)

TCBI with electronic advance Ignition

Transmission 6-speed

Final Drive Tetra-Lever shaft drive

Electronic Rider

Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS System, Kawasaki TRaction Control

Maximum Torque 100.5 lb-ft **Rear Brakes**

Front Brakes

Dual floating 310mm petal-style discs with four-

piston calipers, ABS

Single 270mm petal-style disc, single-piston

caliper, ABS

PERFORMANCE

Front Suspension

Rear Suspension

/ Wheel Travel

/ Wheel Travel

Aids

43mm inverted, telescopic fork with adjustable

rebound damping and spring preload/4.4 in

(KTRC)

DETAILS

Frame Type Monocoque Aluminum

Rake/Trail 26.0/4.4 in

Overall Length 87.8 in

Overall Width 31.1/39.4 wo/w saddlebags

Overall Height 52.9 in/57.7 in (windshield down/up)

Ground

Clearance

4.9 in

Seat Height

32.1 in

Curb Weight

690.2 lb (672.5 w/o saddlebags)*

Fuel Capacity

5.8 gal

Wheelbase

59.8 in

Special Features

Electically adjusted windshield

Color Choices

Metallic Spark Black

Tetra-Lever with stepless rebound damping Warranty adjustment and remote spring preload

36 Month Limited Warranty

adjuster/5.4 in

Front Tire 120/70 ZR-17

Rear Tire 190/50 ZR-17 Kawasaki **Protection Plus™** (optional)

12, 24, or 36 months

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



