MULE PRO-MX™









POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Maximum Torque 42.7 lb-ft @ 5000 rpm

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

35.7 amp

Alternator Output (max)

CAPABILITY

Front Suspension / Double wishbone/8.6 in Wheel Travel

Rear Suspension / Wheel Travel

Rear Tires

Park Brake Type

Double wishbone/9.1 in

25x10.00-12, radial

Independent, Mechanical Disc

Front Tires 25x8.00-12, radial

Steering Rack & Pinion, Tilt steering

Rack & Pillion, Till Steering

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.6 in

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

Fuel Capacity

Cargo Bed Capacity 699 lb (600 lb California models)

33.4 x 44.1 x 9.1 in

9.5 gal

Load Capacity 1200 lb

Seating Capacity 2

Towing Capacity 1500 lb

Lighting (2) Halogen headlights

DETAILS

Overall Length 110.0 in
Overall Width 60.0 in
Overall Height 74.4 in
Curb Weight 1578.8 lb*
Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps

Wheel Type Steel

Color Choices Super Black

Warranty Kawasaki Strong 3-Year Limited Warranty

Kawasaki Protection 12, 2 Plus™ (optional)

12, 24 or 36 months





