## JET SKI® SX-R™ 160











D	N	V	V	F	D
Г	u	II.		Г	П

4-stroke, DOHC, four valves per cylinder, 4-**Engine** 

cylinder inline

**Displacement** 1,498cc

**Bore x Stroke** 83.0 x 69.2mm

Compression

**Ratio** 

10.6:1

Induction Naturally aspirated

**Maximum Boost** N/A

**Cooling System** Inducted water

**Fuel System** DFI® with 60mm throttle body

Ignition TCBI with digital advance

**Starting System** Electric

**Propulsion System** 

148mm jet pump, axial-flow, single stage

3-blade, oval-edge stainless steel **Impeller** 

Thrust 957 lb

## PERFORMANCE

Lubrication Semi-dry sump system

	, and the second se
Oil Capacity	5.8 qt.
Fuel Capacity	6.1 gal.
Load Capacity	1-person

Direct drive from engine

## **DETAILS**

Coupling

**Storage** 

**Capacity** 

**Overall Length** 104.5 in.

**Overall Width** 30.1 in.

**Overall Height** 33.1 in.

**Curb Weight** 551.3 lb.\*

Seating Capacity

Plus™ (optional)

**Color Choices** Ebony/Lime Green

N/A

Warranty 12 Month Limited Warranty

Kawasaki 12, 24, 36, or 48 months **Protection** 





