









D	N	V	V	E	D
г,	u		v	L	1

Engine 4-stroke, air-cooled, single Displacement 49.5cc **Bore x Stroke** 39 x 41.4mm **Compression Ratio** 10.8:1 **Maximum Torque** N/A Keihin PTE 16 **Fuel System** Ignition Solid state CDI **Transmission Automatic CVT Final Drive** 2WD, Chain

Electronic Power Steering (EPS)	No
Turning Radius	8.7 ft
Towing Capacity	N/A
Total Rack Capacity	N/A
Rack Capacity, Front/Rear	N/A
Lighting	N/A

Double cradle, steel

CAPABILITY

Front Suspension / Single A-arm/2.8 in **Wheel Travel** Rear Suspension / Swingarm/2.9 in **Wheel Travel Front Tire** AT 16 x 8-7 tubeless **Rear Tire** AT 16 x 8-7 tubeless **Front Brakes** Dual mechanical drums **Rear Brakes** Hydraulic disc **Ground Clearance** At rear axle - 3.3 in **Starting System** Electric with back-up kick-starter **Fuel Capacity** 1.5 gal

DETAILS

Frame Type

Track Front/Rear	27.2/27.6 in			
Overall Length	55.1 in			
Overall Width	34.1 in.			
Overall Height	34.8 in			
Seat Height	25.0 in			
Curb Weight	249.2 lb*			
Wheelbase	38.0 in			
Instruments	N/A			
Color Choices	Lime Green, Vibrant Blue			
Warranty	12 Month Limited Warranty			
Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months			

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



