

Single 300mm disc with 2-piston calipers (and

Single 240mm disc with single-piston caliper









ABS)

P	N	V	V	F	R
	u	4		_	

Engine 4-Stroke, single cylinder, DOHC

Displacement 652cc

Bore x Stroke 100.0 x 83.0mm

Compression

Ratio

9.8:1

Fuel System DFI w/40mm Throttle Body

Ignition CD

Silition

Transmission 5-speed, return shift with wet multi-disc

manual clutch

Final Drive Sealed Chain

Maximum 39.1 lb.-ft. @ 4,500rpm

Torque

DETAILS

Frame Type Tubular, Semi-Double Cradle

(and ABS)

Rake/Trail 30.0°/4.8 in

Overall Length 89.8 in

Overall Width 38.2 in

Overall Height 57.7/56.3 in (screen hi/lo)

Ground 8.3 in

Clearance

Protection Plus™ (optional)

Front Brakes

Rear Brakes

Seat Height 34.3 in

Curb Weight Non ABS: 456.2 lb / ABS: 460.6 lb*

Fuel Capacity 6.1 gal

Wheelbase 60.6 in

Color Choices Pearl Storm Gray, Pearl Solar Yellow, Candy

Lime Green

Warranty 12 Months

Kawasaki 12, 24, 36 months

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear Suspension / Wheel Travel

Uni-Trak®, single shock with adjustable rebound damping and adjustable spring preload / 8.0 in

Front Tire 90/90-21

Rear Tire 130/80-17

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



