## KLR®650 TRAVELER ABS











Single 300mm disc with 2-piston calipers, ABS

Single 240mm disc with single-piston caliper,

P	N	W	F	R

**Engine** 4-Stroke, single cylinder, DOHC

**Displacement** 652cc

100.0 x 83.0mm **Bore x Stroke** 

Compression

Ratio

9.8:1

**Fuel System** DFI w/40mm Throttle Body

Ignition

**Transmission** 5-speed, return shift with wet multi-disc

manual clutch

**Final Drive** Sealed Chain

Maximum 39.1 lb.-ft. @ 4,500rpm

**Torque** 

## **DETAILS**

**Front Brakes** 

**Rear Brakes** 

**Frame Type** Tubular, Semi-Double Cradle

ABS

30.0°/4.8 in Rake/Trail

**Overall Length** 89.8 in

**Overall Width** 38.2 in

**Overall Height** 57.7/56.3 in (screen hi/lo)

Ground 8.3 in

Clearance

**Curb Weight** 

34.3 in

471.7 lb\*

**Seat Height** 

**Fuel Capacity** 6.1 gal

Wheelbase 60.6 in

**Color Choices** Pearl Solar Yellow

Warranty 12 Months

Kawasaki **Protection** 

Plus™ (optional)

12, 24, 36 months

## **PERFORMANCE**

Front Suspension / Wheel Travel	41mm telescopic fork/ 7.9 in
Rear Suspension / Wheel Travel	Uni-Trak®, single shock with adjustable rebound damping and adjustable spring preload / 8.0 in
Front Tire	90/90-21
Rear Tire	130/80-17

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

