







P	Λ	M	V	С	n
Г	u	V	V	C	π

Engine	4-stroke single, SOHC, air-cooled	
Displacement	112cc	
Bore x Stroke	53.0 x 50.6mm	
Compression Ratio	9.5:1	
Fuel System	18mm Keihin carburetor and screw type throttle limiter on grip housing	
Ignition	DC-CDI	
Transmission	4-speed, return shift, automatic centrifugal and wet, multi-disc clutch	
Final Drive	Chain	

PERFORMANCE

30mm hydraulic telescopic fork/4.3 in
Swingarm with single hydraulic shock/4.3 in
2.50x14
3.00x12

Front Brakes	90mm mechanical drum, cable actuated
Rear Brakes	110mm mechanical drum, rod actuated

DETAILS

(optional)

Frame Type	Backbone frame, high-tensile steel	
Rake/Trail	24.8°/2.0 in	
Overall Length	61.4 in	
Overall Width	25.6 in	
Overall Height	37.6 in	
Ground Clearance	8.5 in	
Seat Height	26.8 in	
Curb Weight	167.5 lb	
Fuel Capacity	1.0 gal	
Wheelbase	42.3 in	
Color Choices	Lime Green	
Warranty	6 Months	
Kawasaki Protection Plus™	12, 24, or 36 months	

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



