## KLX®230R









P	N	V	V	F	R
Г	u	м	ı	E	м

**Engine** 4-stroke single, SOHC, air-cooled

**Displacement** 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Fuel System DFI® with 32mm Keihin throttle body

**Ignition** TCBI Electronic Advance

**Transmission** 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

## PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/9.8 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/9.9 in
Front Tire	80/100-21
Rear Tire	100/100-18

Front Brakes	Single 240mm petal disc with a dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

## **DETAILS**

Frame Type	High-tensile steel, box-section perimeter
Rake/Trail	26.5°/4.4 in
Overall Length	80.5 in
Overall Width	33.1 in
Overall Height	47.2 in
Ground Clearance	11.8 in
Seat Height	36.2 in
Curb Weight	253.6 lb / 262.3 lb. CA model*
Fuel Capacity	1.7 gal
Wheelbase	53.5 in
Color Choices	Lime Green
Warranty	6 Months
Kawasaki Protection Plus™ (optional)	12, 24, or 36 months

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

