## KLX®230R S









P	0	W	ľΕ	R

**Engine** 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Fuel System DFI® with 32mm Keihin throttle body

**Ignition** TCBI Electronic Advance

**Transmission** 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

**Front Brakes** 

Single 240mm petal disc with a dual-piston

caliper

**Rear Brakes** 

Single 220mm petal disc with single-piston

caliper

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

Rear Suspension
/ Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

Front Tire

80/100-21

Rear Tire

100/100-18

## **DETAILS**

Frame Type High-tensile steel, box-section perimeter

Rake/Trail 25.7°/4.3 in

Overall Length 80.1 in

Overall Width 33.1 in

Overall Height 46.3 in

Ground 10.8 in Clearance

Seat Height 35.4 in

Curb Weight 253.6 lb / 262.3 lb. CA model\*

Fuel Capacity 1.7 gal

Wheelbase 53.1 in

Color Choices Lime Green

Warranty 6 Months

Kawasaki Protection Plus™ (optional)

12, 24, or 36 months





