ALL-NEW 2023 KLX® 230SM











POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Fuel System DFI® with 32mm Keihin throttle body

Ignition TCBI Electronic Advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes

Single 300mm petal disc with a dual-piston

caliper (and ABS)

Rear Brakes

Single 220mm petal disc with single-piston

caliper (and ABS)

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear Suspension
/ Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.6 in

110/70-17

Rear Tire

120/70-17

DETAILS

Frame Type High-tensile steel, box-section perimeter

Rake/Trail 27.5°/4.6 in

Overall Length 80.7 in.

Overall Width 32.9 in.

Overall Height 44.1 in.

Ground 9.1 in. Clearance

Seat Height 33.3 in.

Curb Weight NON ABS: 295.5 lb. / 297.7 lb. CA model, ABS:

297.7 lb. / 299.9 lb. CA model *

Fuel Capacity 2.0 gal.

Wheelbase 54.1 in.

Plus™ (optional)

Color Choices Lime Green, Oriental Blue

Warranty 12 Months

Kawasaki 12, 24, or 36 months Protection

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



