KLX®300R









P	N	V	V	F	R
Г	u	w	ı	E	М

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

Compression

Ratio

11.0:1

Fuel System DFI® with 34mm Keihin throttle body

Ignition TCBI Electronic Advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

PERFORMANCE

Front 43mm inverted telescopic fork with adjustable compression damping /11.2 in Wheel Travel

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/11.2 in

Front Tire

Rear Tire

100/100-18

80/100-21

Front Brakes

Single 270mm petal disc with a dual-piston

caliper

Rear Brakes

Single 240mm petal disc with single-piston

caliper

DETAILS

Clearance

Frame Type Tubular, Semi-Double Cradle

Rake/Trail 26.9°/4.3 in

Overall Length 83.5 in

Overall Width 32.5 in

Overall Height 49.2 in

Ground 12.0 in / 11.8 CA model

Seat Height 35.4 in

Curb Weight 282.2 lb / 286.6 lb. CA model*

Fuel Capacity 2.1 gal

Wheelbase 56.5 in

Color Choices Lime Green

Warranty 6 Months

Kawasaki Protection Plus™ (optional) 12, 24, or 36 months

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



