







caliper

caliper

Single 220mm petal disc with dual-piston

Single 184mm petal disc with single-piston

Front Brakes

Rear Brakes

Plus™ (optional)

PUWEK	PUWEK	
Engine	2-stroke single with exhaust power valve (KIPS), liquid-cooled	
Displacement	112cc	
Bore x Stroke	52.5 x 51.6mm	
Compression Ratio	9.9:1 (Low speed)/8.6:1 (High speed)	
Fuel System	28mm Keihin Carburetor	
Ignition	CDI with digital advance	
Transmission	6-speed, return shift, with wet multi-disc manual clutch	
Final Drive	Chain	

PERFORMANCE

Front

Suspension /

Wheel Travel

Rear Suspension

/ Wheel Travel

Front Tire

Rear Tire

	canper
DETAILS	
Frame Type	High-tensile steel perimeter design with subframe member
Rake/Trail	29° /4.3 in
Overall Length	75.6 in
Overall Width	30.1 in
Overall Height	45.3 in
Ground Clearance	13.0 in
Seat Height	34.3 in
Curb Weight	169.7 lb*
Fuel Capacity	1.32 gal
Wheelbase	51.6 in
Color Choices	Lime Green
Warranty	Not Available
Kawasaki Protection	Not Available

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

36mm inverted telescopic cartridge fork with

Uni-Trak® gas charged shock with piggyback

rebound damping plus adjustable spring

preload/10.8 in

70/100-19

90/100-16

reservoir with 24-way compression and 21-way

20-way compression damping/10.8 in



