







POWER	
Engine	4-stroke single, DOHC, liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 x 52.2mm
Compression Ratio	14.1:1
Fuel Cuetem	DEL® with // many Mailein throattle hady and dwall

Fuel SystemDFI® with 44mm Keihin throttle body and dual injectors

Ignition Digital CDI

Transmission 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

PERFORMANCE

Front
Suspension /
Wheel Travel

48mm inverted telescopic coil-spring fork
with 23-way compression damping and 20way rebound damping /12.4 in

New Uni-Trak® with dual-range (2.25 turns

Rear
Suspension /
Wheel Travel
New Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and

adjustable preload/12.4 in

Front Tire 80/100-21

Rear Tire 110/100-18

Front Brakes
Single semi-floating 270mm Braking® petal disc with dual-piston caliper

Rear Brakes Single 240mm Braking® petal disc with single-piston caliper

Aluminum perimeter

DETAILS

Frame Type

Kawasaki

Protection Plus™

(optional)

Rake/Trail	27.8° / 4.8 in
Overall Length	85.4 in
Overall Width	32.3 in
Overall Height	49.6 in
Ground Clearance	13.0 in
Seat Height	37.2 in
Curb Weight	230.1 lb without fuel / 240.2 lb
Fuel Capacity	1.64 gal
Wheelbase	58.3 in
Color Choices	Lime Green
Warranty	Not Available
- 0	

Not Available

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



