







POWER

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 449cc

Bore x Stroke 96.0 x 62.1mm

Compression

Transmission

Ratio

12.5:1

Fuel System DFI® with 44mm Keihin throttle body

Ignition Digital CDI with 3 Coupler Options

5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation

Final Drive Chain

PERFORMANCE

Front
Suspension /
Wheel Travel

49mm inverted telescopic coil-spring fork
with 16-way compression damping and 16way rebound damping/12.0 in

Rear
Suspension /
Wheel Travel
Uni-Trak® gas charged shock with piggyback reservoir with dual-range (4 turns stepless high speed/19-way low-speed) compression damping, 22-way rebound damping and

adjustable preload/12.1 in

Front Tire 80/100-21

Rear Tire 120/80-19

Front Brakes Single semi-floating 270mm Braking® petal disc with dual-piston caliper

Rear Brakes Single 250mm Braking® petal disc with single-piston caliper

DETAILS

Kawasaki

Protection Plus™

(optional)

Frame Type	Aluminum perimeter
Rake/Trail	27.6° / 4.8 in
Overall Length	86.0 in
Overall Width	32.3 in
Overall Height	49.8 in
Ground Clearance	13.4 in
Seat Height	37.6 in
Curb Weight	233.2 lb without fuel / 243.3 lb
Fuel Capacity	1.64 gal
Wheelbase	58.5 in
Color Choices	Lime Green
Warranty	Not Available

Not Available

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



