







P	N	W	FI	R
	U	W	EI	П

2-stroke single, liquid-cooled **Engine Displacement** 64cc 45.5 x 41.6mm **Bore x Stroke** Compression 8.4:1 Ratio **Fuel System** 24mm Mikuni carburetor Ignition CDI with digital advance **Transmission** 6-speed, return shift, with wet multi-disc manual clutch

PERFORMANCE

Chain

Final Drive

Front
Suspension / Wheel Travel

Rear
Suspension / Wheel Travel

Rear
Suspension / Wheel Travel

Front Tire

33mm leading axle telescopic fork with 4-way rebound damping/8.3 in

Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in

60/100-14

Rear Tire

80/100-12

Front Brakes	Single 180mm disc with single-piston caliper
Rear Brakes	Single 180mm disc with single-piston caliper

DETAILS

DLIMILO	
Frame Type	High-tensile steel semi-double cradle
Rake/Trail	27° / 2.4 in
Overall Length	62.6 in
Overall Width	29.9 in
Overall Height	37.6 in
Ground Clearance	12.0 in
Seat Height	29.9 in
Curb Weight	132.2 lb
Fuel Capacity	1.0 gal
Wheelbase	44.1 in
Color Choices	Lime Green
Warranty	Not Available
Kawasaki Protection Plus™ (optional)	Not Available

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



