PNWFR









caliper

Single 220mm petal disc with dual-piston

Single 184mm petal disc with single-piston

Front Brakes

Rear Brakes

1 OWLK		
Engine	2-stroke single with exhaust power valve (KIPS), liquid-cooled	
Displacement	84cc	
Bore x Stroke	48.5 x 45.8mm	
Compression Ratio	10.9:1 (low speed) - 9.0:1 (high speed)	
Fuel System	28mm Keihin carburetor	
Ignition	CDI with digital advance	
Transmission	6-speed, return shift, with wet multi-disc manual clutch	
Final Drive	Chain	

	caliper
DETAILS	
Frame Type	High-tensile steel perimeter design with subframe member
Rake/Trail	29° /3.8 in
Overall Length	72.0 in
Overall Width	30.1 in
Overall Height	43.3 in
Ground Clearance	11.4 in
Seat Height	32.7 in
Curb Weight	165.3 lb
Fuel Capacity	1.32 gal
Wheelbase	49.8 in
Color Choices	Lime Green
Warranty	Not Available
Kawasaki Protection Plus™ (optional)	Not Available

Front 36mm inverted telescopic cartridge fork with Suspension / **Wheel Travel**

PERFORMANCE

20-way compression damping/10.8 in

Rear Suspension Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, / Wheel Travel plus adjustable spring preload/10.8 in

Front Tire 70/100-17

Rear Tire 90/100-14

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



