MULE™ 4010 TRANS4x4® FE









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled

Displacement 617cc

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Maximum Torque 34.7 lb-ft @ 2500 rpm

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Fuel Capacity 6.3 gal

Ground Clearance

Turning Radius 12.8 ft

50.4 x 47.6 x 11.2 in (2-person) 30.3 x 47.6 x 11.2 in (4-**Cargo Bed** Dimensions (LxWxH)

7.7 in

Cargo Bed Capacity 800 lb (2-person) 401 lb (4-person)

Load Capacity 1330 lb

Seating Capacity 2-4

Towing Capacity

Lighting (2) Halogen headlights (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension /

Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10 **Rear Tires** 23x11.00-10

Park Brake Type Independent, Mechanical Drum

Steering

Front Brakes

Electric Power Steering (EPS)

Drum

Rear Brakes Drum **DETAILS**

Overall Length

128.5 in

Overall Width 58.5 in

Overall Height 78.1 in

Curb Weight 1614.1 lb*

Wheelbase 85.2 in

Parking brake warning light, coolant temperature Instruments

warning light, horn, 12V DC outlet, fuel gauge, hour

Wheel Type Steel

Color Choices Bright White

Warranty Kawasaki Strong 3-Year Limited Warranty

Kawasaki 12, 24 or 36 months

Protection Plus™ (optional)

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



