MULE PRO-FXT™









D	N	۱	AI	II	С	D
Г	u	и	и.	П	C.	м

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Maximum Torque 48.0 lb-ft @ 3500 rpm

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 75 amp

(max)

Ground Clearance 10.2 in

Turning Radius 16.0 ft

Fuel Capacity

Cargo Bed "42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-

7.9 gal

Dimensions (LxWxH) perso

Cargo Bed Capacity 999 lb (3-person), 350 lb (6-person), (348 lb for California

models)

Load Capacity 1616.3 lb (1263.5 for California models)

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights

CAPABILITY

Front Suspension / Wheel Travel Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires

26x9.00-12, radial 26x11.00-12, radial

Rear Tires
Park Brake Type

Independent, Mechanical Disc

.

_

Steering

Rack-and-pinion

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1887.5 lb*

Wheelbase 92.3 in

Instruments N

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator,

oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and

parking indicators, seatbelt reminder lamps

Wheel Type Steel

Color Choices Super Black

Warranty Kawasaki Strong 3-Year Limited Warranty

Kawasaki Protection 12, 24 or 36 months Plus™ (optional)

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



