## MULE PRO-FXT RANCH EDITION PLATINUM









D	N	V	v	С	D
Г	u	v	V	C	П

**Engine** 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

**Bore x Stroke** 2.83x2.62 in

**Compression Ratio** 

**Maximum Torque** 48.0 lb-ft @ 3500 rpm

**Fuel System** DFI® with 34mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R) Transmission

Selectable 2WD/4WD, shaft. Dual mode rear differential with **Final Drive** 

differential lock

**Engine Braking** 

**Alternator Output** (max)

75 amp

## CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

**Front Tires** 26x9.00-12, radial

**Rear Tires** 26x11.00-12, radial

Park Brake Type

Independent, Mechanical Disc

Steering

Electric Power Steering (EPS), Tilt steering

**Front Brakes** 

Dual Disc, 2 piston caliper

**Rear Brakes** 

Dual Disc, 1 piston caliper

**Ground Clearance** 10.0 in

**Fuel Capacity** 7.9 gal

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-person)

Dimensions (LxWxH) **Cargo Bed Capacity** 

**Turning Radius** 

999 lb (3-person), 350 lb (6-person), (348 lb for California models)

16.0 ft

**Load Capacity** 1616.3 lb (1263.5 for California models)

**Seating Capacity** 3-person (1 row), 6 person (2 row)

**Towing Capacity** 2000 lb

Lighting (4) LED headlights

## **DETAILS**

**Overall Length** 140.2 in **Overall Width** 64.0 in

**Overall Height** 79.5 in

**Curb Weight** 2035.2 lb\*

Wheelbase 92.3 in

Multi-function display includes digital speedometer, fuel Instruments

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

Wheel Type Alloy

**Color Choices** Metallic Rustic Bronze

Warranty Kawasaki Strong 3-Year Limited Warranty

**Kawasaki Protection** Plus™ (optional)

12, 24 or 36 months

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



