UPDATED 2023

NINJA® 650 KRT EDITION











POWER

Engine 4-stroke, Parallel Twin, DOHC, 8-valve, liquid

cooled

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

10.8:1

Fuel System DFI® with dual 36mm Keihin throttle bodies

Ignition TCBI with electronic advance

Transmission 6-speed

Final Drive Sealed chain

Electronic Rider Kawasaki TRaction Control (KTRC - 2 Modes),

Aids

Front Brakes

Dual 300mm petal-type discs and 2-piston

calipers (and ABS)

Rear Brakes Single 2

Single 220mm petal-type disc and single-

piston caliper (and ABS)

NON ABS: 419.0 lb / ABS: 423.4 lb*

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear Suspension / Wheel Travel

Horizontal back-link with adjustable spring preload/5.1 in

Front Tire 120/70x17

Rear Tire 160/60x17

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 24.0°/3.9 in

Overall Length 80.9 in

Overall Width 29.1 in

Overall Height 45.1 in

Ground 5.1 in

Clearance
Seat Height

Curb Weight

Protection Plus™ (optional) 31.1 in

Fuel Capacity 4.0 gal

Wheelbase 55.5 in

Color Choices Lime Green/Ebony

Warranty 12 Month Limited Warranty

Kawasaki 12, 24, 36 or 48 months

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



