

UPDATED 2023

NINJA H2® SX SE

RYMCO
POWERSPORTS



EMERALD BLAZED GREEN/METALLIC DIABLO BLACK/
METALLIC GRAPHITE GRAY



POWER

Engine	4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
Compression Ratio	11.2:1
Fuel System	DFI® w/40mm throttle bodies; Kawasaki Supercharger
Ignition	TCBI w/ digital advance
Transmission	6-speed, manual, return shift, dog ring
Final Drive	Sealed chain
Electronic Rider Aids	Advanced Rider Assistance Systems (ARAS): Forward Collision Warning (FCW), Blind-Spot Detection (BSD), Adaptive Cruise Control (ACC), Vehicle Hold Assist (VHA), Kawasaki Electronic Control Suspension with Showa Skyhook Technology (KECS), Power Modes, Integrated Riding Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS) (dual direction), LED Cornering Lights, Grip Heaters, Tire Pressure Monitoring System (TPMS)
Maximum Torque	101.0 lb-ft.

Rear Tire	190/55 ZR17 (75W)
Front Brakes	Dual radial-mount, opposed 4-piston Brembo Stylema® monobloc calipers, dual semi-floating 320mm discs, KIBS ABS
Rear Brakes	Opposed 2-piston calipers, single 250mm disc, KIBS ABS

DETAILS

Frame Type	Trellis, high-tensile steel, with swingarm mounting plate
Rake/Trail	24.7° /4.1 in.
Overall Length	85.6 in.
Overall Width	31.1 in.
Overall Height	49.6 in.
Ground Clearance	5.1 in.
Seat Height	32.9 in.
Curb Weight	590.9 lb*
Fuel Capacity	5.0 gal.
Wheelbase	58.3 in.
Special Features	6.5" Full-Color TFT Instrumentation, Kawasaki SPIN infotainment app, All-LED lighting, KIPASS, Highly Durable Paint
Color Choices	Emerald Blazed Green/Metallic Diablo Black/Metallic Graphite Gray
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36 or 48 months

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/4.7 in.
Rear Suspension / Wheel Travel	Uni-Trak®, BFRC lite gas charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.5 in.
Front Tire	120/70 ZR17 (58W)

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2022 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.