









190/65 ZR17 V01R slick

KIBS ABS

ABS

Dual radial-mount, opposed 4-piston Brembo Stylema® calipers, dual semi-floating 330mm discs,

Opposed 2-piston calipers, single 250mm disc, KIBS

POWER

Engine Liquid -cooled, 4-stroke, In-Line Four, DOHC, 16-valve

Displacement 998cc

76.0 x 55.0mm **Bore x Stroke**

Compression Ratio 8.3:1

DFI® with 50mm throttle bodies (4) with dual **Fuel System**

injection; Kawasaki Supercharger

Ignition Digital

Transmission 6-speed, return, dog-ring

Final Drive Sealed chain

Electronic Rider

Aids

Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS) (upshift & downshift),

Öhlins Electronic Steering Damper

Maximum Torque 121.5 lb-ft @ 12,500 rpm

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Frame Type Trellis, high-tensile steel, with swingarm mounting plate

25.1° / 4.3 in Rake/Trail

Overall Length 81.5 in

Overall Width 33.5 in

Overall Height 45.7 in

Ground Clearance 5.1 in

Seat Height 32.7 in

Curb Weight 476.3 lb*

Fuel Capacity

(optional)

Wheelbase 57.1 in

Special Features Aerodynamic downforce generating devices, Highly

Durable Paint, Analog Tach & LCD instrumentation

Color Choices Mirror Coated Matte Spark Black

4.5 gal

Warranty N/A

Kawasaki Protection Plus™

N/A

PERFORMANCE

Front Suspension / **Wheel Travel**

43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

Rear Suspension / Wheel Travel

Uni-Trak®, Öhlins TTX36 gas charged shock with piggyback reservoir, 30-way compression and rebound damping and adjustability, and hand-turn spring preload adjustability and top-outspring/5.3 in

Front Tire

120/60 ZR17 V01F slick





