VULCAN® 1700 VAQUERO® ABS









ACT II ABS



Dual 300mm discs, dual four-piston calipers, K-

Single 300mm disc, twin-piston caliper, K-ACT II

D	N	V	V	F	D
Г	U	W	v	Г	П

Engine 4-stroke, 52-degree V-twin, liquid-cooled

Displacement 1,700cc/103.7 cu in

Bore x Stroke 102.0 x 104.0mm

Compression

Ratio

9.5:1

Fuel System DFI 42mm Throttle Bodies (2)

Ignition TCBI w/ Electronic Advance

Transmission 6-speed with overdrive and positive neutral

finder

Final Drive Carbon fiber-reinforced belt

Electronic Rider Electronic cruise control, Kawasaki Advanced

Aids Coactive-Braking Technology (K-ACT II) ABS

Maximum Torque 107.6 lb-ft @ 2750 rpm

DETAILS

Front Brakes

Rear Brakes

Frame Type Steel, double-cradle with box-section single-tube backbone

Rake/Trail 30/7.0 in

Overall Length 98.8 in

Overall Width 38.2 in

Overall Height 50.8 in

Ground Clearance 5.7 in

Seat Height 28.7 in

Curb Weight 844.5 lb*

Fuel Capacity 5.3 gal

Wheelbase 65.6 in

Protection Plus™ (optional)

Special Features Integrated audio system with SiriusXM ® Radio

compatibility

Color Choices Metallic Matte Graphenesteel Gray

Warranty 36 Month Limited Warranty

Kawasaki 12, 24, 36 months

PERFORMANCE

Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel

Swingarm with twin air-assisted shocks, with 4-way rebound damping/3.1 in

Front Tire 130/90-16

Rear Tire 170/70-16

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



