

2023

VULCAN® 1700 VOYAGER® ABS

RYMCO
 POWERSPORTS


Kawasaki
 Let the good times roll®


PEARL STORM GRAY/EBONY



POWER

Engine	4-stroke, 52-degree V-twin, liquid-cooled
Displacement	1,700cc/103.7 cu in
Bore x Stroke	102.0 x 104.0mm
Compression Ratio	9.5:1
Fuel System	DFI 42mm Throttle Bodies (2)
Ignition	TCBI w/ Electronic Advance
Transmission	6-speed with overdrive and positive neutral finder
Final Drive	Carbon fiber-reinforced belt
Electronic Rider Aids	Electronic cruise control, Kawasaki Advanced Coactive-Braking Technology (K-ACT II) ABS
Maximum Torque	107.6 lb-ft @ 2750 rpm

PERFORMANCE

Front Suspension / Wheel Travel	45mm Showa telescopic fork/5.5 in
Rear Suspension / Wheel Travel	Swingarm with twin air-assisted shocks, with 4-way rebound damping/3.1 in
Front Tire	130/90-16
Rear Tire	170/70-16

Front Brakes	Dual 300mm discs, dual four-piston calipers, K-ACT II ABS
Rear Brakes	Single 300mm disc, twin-piston caliper, K-ACT II ABS

DETAILS

Frame Type	Steel, double-cradle with box-section single-tube backbone
Rake/Trail	30/7.0 in
Overall Length	100.8 in
Overall Width	39.2 in
Overall Height	61.0 in
Ground Clearance	5.3 in
Seat Height	28.7 in
Curb Weight	895.2 lb
Fuel Capacity	5.3 gal
Wheelbase	65.6 in
Special Features	Integrated audio system with SiriusXM® and intercom headset compatibility
Color Choices	Pearl Storm Gray/Ebony
Warranty	36 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36 months

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2022 Kawasaki Motors Corp., U.S.A.
 Specifications subject to change. Visit Kawasaki.com for full product details.