
## **VULCAN® 900 CLASSIC**











n	n	W	v	Г	n
r	U	V	V	E	ĸ

**Engine** 4-stroke, 55-degree V-twin, liquid-cooled

**Displacement** 903cc/55.10 cu in

Bore x Stroke 88.0 x 74.2mm

Compression

Ratio

9.5:1

**Fuel System** DFI 34mm Throttle Bodies (2), with sub-throttle

41mm Showa telescopic fork/5.9 in

Uni-Trak® swingarm, 7-way adjustable spring

valves

Ignition TCBI w/ Electronic Advance

**Transmission** 5-speed with positive neutral finder

Final Drive Kevlar-reinforced belt

Maximum 58.2 lb-ft @ 3500 rpm

Torque

Front

Suspension / Wheel Travel

**Rear Suspension** 

/ Wheel Travel

## Rear Brakes

**Front Brakes** 

Single 300mm hydraulic disc

ar Brakes Single 270mm hydraulic disc

## **DETAILS**

**Frame Type** Semi-double cradle, high-tensile steel

Rake/Trail 32/6.3 in

Overall Length 97.0 in

Overall Width 39.6 in

Overall Height 41.9 in

Ground Clearance 5.3 in

Seat Height 26.8 in

Curb Weight 619.6 lb\*

Fuel Capacity 5.3 gal

Wheelbase 64.8 in

**Color Choices** 

Metallic Spark Black/Metallic Magnesium Gray

Warranty

12 Month Limited Warranty

preload/4.1 in

Front Tire 130/90-16

**Rear Tire** 180/70-15

**PERFORMANCE** 

Kawasaki Protection Plus™ (optional) 12, 24, 36 or 48 months

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



