VULCAN® S CAFE











Single 300mm disc with twin-piston caliper

Single 250mm disc with single-piston caliper

| P | N | V | N | F | R |
|---|---|---|---|---|---|
| | u | | м | _ | • |

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

10.8:1

Fuel System DFI 38mm Throttle Bodies (2), with sub-throttle

valves

Ignition TCBI w/ Electronic Advance

Transmission 6-speed with positive neutral finder

Final Drive Sealed Chain

Maximum 46.3 lb-ft @ 6600 rpm

Torque

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Frame Type High-tensile steel diamond frame

160/60x17

Rake/Trail 31/4.7 in

Overall Length 90.9 in

Overall Width 34.6 in

Overall Height 44.5 in

Ground Clearance

Protection Plus™ (optional) 5.1 in

Seat Height 27.8 in

Curb Weight 496.1 lb

Fuel Capacity 3.7 gal

Wheelbase 62.0 in

Color Choices Pearl Storm Gray/Ebony

Warranty 12 Month Limited Warranty

Kawasaki 12, 24, 36 or 48 months

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear Suspension
/ Wheel Travel

Lay-down offset rear shock with linkage and adjustable preload/3.2 in

120/70x18

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



