









_	_				_
-	N	34	7.1		-
v		м	٧Л	-	u
		w			•

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 399cc

70.0 x 51.8mm

Compression 11.5:1

DFI® with 32mm throttle bodies

**Ignition** TCBI with digital advance

**Transmission** 6-speed, return shift

Final Drive Sealed chain

Maximum Torque

**Fuel System** 

28.0 lb-ft @ 8,000 rpm

## **PERFORMANCE**

Front Suspension / Wheel Travel	Telescopic fork/4.7 in
Rear Suspension / Wheel Travel	Uni-Trak® swingarm/5.1 in
Front Tire	110/70-17M/C 54H
Rear Tire	150/60-17M/C 66H

Front Brakes	Single 310mm disc, ABS
Rear Brakes	Single 220mm disc, ABS

## **DETAILS**

DLINILO	
Frame Type	Trellis, high-tensile steel
Rake/Trail	24.5°/3.6 in
Overall Length	78.3 in
Overall Width	31.5 in
Overall Height	41.5 in
Ground Clearance	5.7 in
Seat Height	30.9 in
Curb Weight	363.8 lb*
Fuel Capacity	3.7 gal
Wheelbase	53.9 in
Color Choices	Metallic Matte Graphenesteel Gray/Metallic Spark Black, Pearl Robotic White/Metallic Matte Graphenesteel Gray
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 26 or 48 months

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



