







METALLIC PHANTOM SILVER/METALLIC CARBON GRAY



METALLIC SPARK BLACK/METALLIC GRAPHITE GRAY/ METALLIC FLAT SPARK BLACK



D	n	M	V	С	D
Г	U	V	٧	C	Ν

4-stroke, 4-cylinder, DOHC, 16-valve, liquid-cooled **Engine**

Displacement 948cc

Bore x Stroke 73.4 x 56.0mm

Compression

Ratio

11.8:1

Fuel System DFI® with 36mm Keihin throttle bodies

Ignition TCBI with electronic advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Integrated Riding Modes, Kawasaki Traction

Control (KTRC), Power Modes (2)

Maximum Torque

73.1 lb-ft @ 7,700 rpm

PERFORMANCE

Front Suspension 41mm inverted fork with rebound damping / Wheel Travel adjustability/4.7 in Rear Suspension / Horizontal back-link, stepless rebound damping,

adjustable spring preload/5.5 in

Wheel Travel

Front Tire

120/70 ZR17

Rear Tire

180/55 ZR17

Front Brakes Dual 300mm petal-style discs with four-piston

calipers, ABS

Rear Brakes Single 250mm petal-style disc with single-piston

caliper, ABS

Frame Type Trellis, high tensile steel

24.9° / 4.3 in Rake/Trail

Overall Length 81.5 in

Overall Width 32.5 in

Overall Height 42.5 in

Ground Clearance 5.7 in

Seat Height 31.5 in

Curb Weight 467.5 lb*

Fuel Capacity 4.5 gal

Wheelbase 57.3 in

Special Features Rideology the App Smartphone Connectivity, TFT

Instrumentation

Color Choices Metallic Spark Black/Metallic Graphite Gray/

Metallic Flat Spark Black, Metallic Phantom Silver/

Metallic Carbon Gray

Warranty 12 Month Limited Warranty

Kawasaki Protection Plus™

(optional)

12, 24, 36 or 48 months





