









D	N	W	IΕ	D
Г	U	W	ľ	П

Engine 4-stroke, 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 948cc

Bore x Stroke 73.4 x 56.0mm

Compression

Ratio

11.8:1

Fuel System DFI® with 36mm Keihin throttle bodies

Ignition TCBI with electronic advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider Aids Integrated Riding Modes, Kawasaki Traction

Control (KTRC), Power Modes (2)

Maximum Torque 73.1 lb-ft @ 7,700 rpm

PERFORMANCE

Front Suspension / Wheel Travel 41mm inverted fork with rebound damping adjustability/4.7 in

Rear Suspension
/ Wheel Travel

Horizontal back-link, Ohlins S46 gas-charged shock with adjustable rebound damping, remote

adjustable spring preload/5.5 in

Front Tire 120/70 ZR17

Rear Tire 180/55 ZR17

Front Brakes

Dual semi-floating 300mm Brembo discs with dual radial-mount, Brembo M4.32 monobloc,

four-piston calipers, ABS

Rear Brakes Single 250mm petal-style disc with single-piston

caliper, ABS

DETAILS

Frame Type Trellis, high tensile steel

Rake/Trail 24.9°/4.3 in

Overall Length 81.5 in

Overall Width 32.5 in

Overall Height 43.9 in

Ground Clearance 5.7 in

Seat Height 31.5 in

Curb Weight 469.7 lb*

Fuel Capacity 4.5 gal

Wheelbase 57.3 in

(optional)

Special Features Rideology the App Smartphone Connectivity, TFT

Instrumentation

Color Choices Metallic Spark Black/Metallic Matte Graphenesteel Gray/Candy Lime Green

, ,

Warranty 12 Month Limited Warranty

Kawasaki 12, 24, 36 or 48 months **Protection Plus™**

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.



